

## FLNAB Flood Light/Low Bay Light series

Common Specifications :

Input	AC100~277V, 50~60Hz
Power Factor	(AC100~240V)>0.9 ; (AC277V)>0.8
Ingress Protection	IP66
CCT	5000K(3000K,6000K available)
Beam Angle	149°×72°/145°×(17°+55°)/15°/30°/60°/30°×15°
Operating Temperature	-30°C~50°C
Power Certifications	CE/CB/PSE/UL
Light Certifications	CE/CB
Guarantee	2 years

Model No.	FLN038ABLB	FLN030ABLB	FLN075ABLB	FLN060ABLB	FLN113ABLB	FLN090ABLB
LED Source	CREE	NICHIA	CREE	NICHIA	CREE	NICHIA
Lm	3000	2700	6000	5400	9000	8100
Lm/W	80	90	80	90	80	90
Power Input	37.5	30	75	60	112.5	90
Weight	2.5Kg		4.5Kg		6.5Kg	
Dimensions	150×305×156.5mm		245×305×156.5mm		341×305×156.5mm	
Picture						
Model No.	FLN038AB	FLN030AB	FLN075AB	FLN060AB		
LED Source	CREE	NICHIA	CREE	NICHIA		
Lm	3000	2700	6000	5400		
Lm/W	80	90	80	90		
Power Input	37.5	30	75	60		
Weight	2.5Kg		4.5Kg			
Dimensions	244.5×305×128.1mm		340×305×128.1mm			
Picture						