

**SMD3528 燈條(60pcs/M)**

型號 Items	顏色 Color	LED Parameters			亮度 mcd(or Lm)	材質 Material	功率 Watt/M	尺寸 Dimensions	備註 Note
		Type	Quantity	nm/K					
<b>裸燈帶IP20</b>									
LB3528-60R	R	SMD3528	60pcs/m	620-625	300-500	FPC	4.8w/m	8*5000mm	DC12V/0.4A or DC24V/0.2A, viewing angle120°, 95g/role,3M twin adhesive
LB3528-60Y	Y	SMD3528	60pcs/m	587-592	500-800	FPC	4.8w/m	8*5000mm	
LB3528-60B	B	SMD3528	60pcs/m	465-470	300-500	FPC	4.8w/m	8*5000mm	
LB3528-60G	G	SMD3528	60pcs/m	520-525	1000-1200	FPC	4.8w/m	8*5000mm	
LB3528-60W	W	SMD3528	60pcs/m	6000±250K	2100~2400Lm	FPC	4.8w/m	8*5000mm	
LB3528-60WW	WW	SMD3528	60pcs/m	3000±200K	2000~2300Lm	FPC	4.8w/m	8*5000mm	
<b>套管+灌膠防水IP68</b>									
LB3528-60R68	R	SMD3528	60pcs/m	620-630	300-500	FPC	4.8w/m	10*5000mm	DC12V/0.4A or DC24V/0.2A, viewing angle120°, 360g/role,3M twin adhesive
LB3528-60Y68	Y	SMD3528	60pcs/m	587-592	500-800	FPC	4.8w/m	10*5000mm	
LB3528-60B68	B	SMD3528	60pcs/m	465-470	300-500	FPC	4.8w/m	10*5000mm	
LB3528-60G68	G	SMD3528	60pcs/m	520-525	1000-1200	FPC	4.8w/m	10*5000mm	
LB3528-60W68	W	SMD3528	60pcs/m	6000±250K	2100~2400Lm	FPC	4.8w/m	10*5000mm	
LB3528-60WW68	WW	SMD3528	60pcs/m	3000±200K	2000~2300Lm	FPC	4.8w/m	10*5000mm	

**SMD3528 燈條(120pcs/M)**

型號 Items	顏色 Color	LED Parameters			亮度 mcd(or Lm)	材質 Material	功率 Watt/M	尺寸 Dimensions	備註 Note
		Type	Quantity	nm/K					
<b>裸燈帶IP20</b>									
LB3528-120R	R	SMD3528	120pcs/m	620-630	600-1000	FPC	9.6w/m	8*5000mm	DC12V/0.8A or DC24V/0.4A, viewing angle120°, 135g/role,3M twin adhesive
LB3528-120Y	Y	SMD3528	120pcs/m	587-592	1000-1600	FPC	9.6w/m	8*5000mm	
LB3528-120B	B	SMD3528	120pcs/m	465-470	600-1000	FPC	9.6w/m	8*5000mm	
LB3528-120G	G	SMD3528	120pcs/m	520-525	2000-2400	FPC	9.6w/m	8*5000mm	
LB3528-120W	W	SMD3528	120pcs/m	6000±250K	4200~4800Lm	FPC	9.6w/m	8*5000mm	
LB3528-120WW	WW	SMD3528	120pcs/m	3000±200K	4000~4600Lm	FPC	9.6w/m	8*5000mm	
<b>套管+灌膠防水IP68</b>									
LB3528-120R68	R	SMD3528	120pcs/m	620-630	600-1000	FPC	9.6w/m	10*5000mm	DC12V/0.8A or DC24V/0.4A, viewing angle120°, 380g/role,3M twin adhesive
LB3528-120Y68	Y	SMD3528	120pcs/m	587-592	1000-1600	FPC	9.6w/m	10*5000mm	
LB3528-120B68	B	SMD3528	120pcs/m	465-470	600-1000	FPC	9.6w/m	10*5000mm	
LB3528-120G68	G	SMD3528	120pcs/m	520-525	2000-2400	FPC	9.6w/m	10*5000mm	
LB3528-120W68	W	SMD3528	120pcs/m	6000±250K	4200~4800Lm	FPC	9.6w/m	10*5000mm	
LB3528-120WW68	WW	SMD3528	120pcs/m	3000±200K	4000~4600Lm	FPC	9.6w/m	10*5000mm	

### SMD2835 燈條 (60pcs/M)

型號 Items	顏色 Color	LED Parameters			亮度 mcd(or Lm)	材質 Material	功率 Watt/M	尺寸 Dimensions	備註 Note
		Type	Quantity	nm/K					
裸燈帶IP20									
LB2835-60R	R	SMD2835	60pcs/m	620-630	1800-2400	FPC	6w/m	8*5000mm	DC12V/0.6A or DC24V/0.3A, viewing angle120°, 85g/role,3M twin adhesive
LB2835-60Y	Y	SMD2835	60pcs/m	587-592	2000-2500	FPC	6w/m	8*5000mm	
LB2835-60B	B	SMD2835	60pcs/m	465-470	1000-1500	FPC	6w/m	8*5000mm	
LB2835-60G	G	SMD2835	60pcs/m	520-525	4000-5000	FPC	6w/m	8*5000mm	
LB2835-60W	W	SMD2835	60pcs/m	6000±250K	6600~7200Lm	FPC	6w/m	8*5000mm	
LB2835-60WW	WW	SMD2835	60pcs/m	3000±200K	6000~6600Lm	FPC	6w/m	8*5000mm	
套管+灌膠防水IP68									
LB2835-60R68	R	SMD2835	60pcs/m	620-630	1800-2400	FPC	6w/m	10*5000mm	DC12V/0.6A or DC24V/0.3A, viewing angle120°, 320g/role,3M twin adhesive
LB2835-60Y68	Y	SMD2835	60pcs/m	587-592	2000-2500	FPC	6w/m	10*5000mm	
LB2835-60B68	B	SMD2835	60pcs/m	465-470	1000-1500	FPC	6w/m	10*5000mm	
LB2835-60G68	G	SMD2835	60pcs/m	520-525	4000-5000	FPC	6w/m	10*5000mm	
LB2835-60W68	W	SMD2835	60pcs/m	6000±250K	6600~7200Lm	FPC	6w/m	10*5000mm	
LB2835-60WW68	WW	SMD2835	60pcs/m	3000±200K	6000~6600Lm	FPC	6w/m	10*5000mm	

### SMD2835 燈條 (120pcs/M)

型號 Items	顏色 Color	LED Parameters			亮度 mcd(or Lm)	材質 Material	功率 Watt/M	尺寸 Dimensions	備註 Note
		Type	Quantity	nm/K					
裸燈帶IP20									
LB2835-120R	R	SMD2835	120pcs/m	620-630	3600~4800	FPC	12w/m	8*5000mm	DC12V/0.6A or DC24V/0.3A, viewing angle120°, 100g/role,3M twin adhesive
LB2835-120Y	Y	SMD2835	120pcs/m	587-592	4000~5000	FPC	12w/m	8*5000mm	
LB2835-120B	B	SMD2835	120pcs/m	465-470	2000~3000	FPC	12w/m	8*5000mm	
LB2835-120G	G	SMD2835	120pcs/m	520-525	8000~10000	FPC	12w/m	8*5000mm	
LB2835-120W	W	SMD2835	120pcs/m	6000±250K	13200~14400Lm	FPC	12w/m	8*5000mm	
LB2835-120WW	WW	SMD2835	120pcs/m	3000±200K	12000~13200Lm	FPC	12w/m	8*5000mm	
套管+灌膠防水IP68									
LB2835-120R68	R	SMD2835	120pcs/m	620~630	3600~4800	FPC	12w/m	10*5000mm	DC12V/0.6A or DC24V/0.3A, viewing angle120°, 330g/role,3M twin adhesive
LB2835-120Y68	Y	SMD2835	120pcs/m	587~592	4000~5000	FPC	12w/m	10*5000mm	
LB2835-120B68	B	SMD2835	120pcs/m	465~470	2000~3000	FPC	12w/m	10*5000mm	
LB2835-120G68	G	SMD2835	120pcs/m	520~525	8000~10000	FPC	12w/m	10*5000mm	
LB2835-120W68	W	SMD2835	120pcs/m	6000±250K	13200~14400Lm	FPC	12w/m	10*5000mm	
LB2835-120WW68	WW	SMD2835	120pcs/m	3000±200K	12000~13200Lm	FPC	12w/m	10*5000mm	

### SMD5050 燈條(60pcs/M)

型號 Items	顏色 Color	LED Parameters			亮度 mcd(or Lm)	材質 Material	功率 Watt/M	尺寸 Dimensions	備註 Note
		Type	Quantity	nm/K					
裸燈帶IP20									
LB5050-60R	R	SMD5050	60pcs/m	620-630	1800-2400	FPC	14.4w/m	10*5000mm	DC12V/1.2A or DC24V/0.6A, viewing angle120°, 110g/role,3M twin adhesive
LB5050-60Y	Y	SMD5050	60pcs/m	587-592	2000-2500	FPC	14.4w/m	10*5000mm	
LB5050-60B	B	SMD5050	60pcs/m	465-470	1000-1500	FPC	14.4w/m	10*5000mm	
LB5050-60G	G	SMD5050	60pcs/m	520-525	4000-5000	FPC	14.4w/m	10*5000mm	
LB5050-60W	W	SMD5050	60pcs/m	6000±250K	6600~7200Lm	FPC	14.4w/m	10*5000mm	
LB5050-60WW	RW	SMD5050	60pcs/m	3000±200K	6000~6600Lm	FPC	14.4w/m	10*5000mm	
LB5050-60RGB	RGB	SMD5050	60pcs/m	523 G:520 B:4	R:600 G:1400 B:500	FPC	14.4w/m	10*5000mm	

套管+灌膠防水IP68									
LB5050-60R68	R	SMD5050	60pcs/m	620-630	1800-2400	FPC	14.4w/m	12*5000mm	DC12V/1.2A or DC24V/0.6A, viewing angle120°, 360g/role,3M twin adhesive
LB5050-60Y68	Y	SMD5050	60pcs/m	587-592	2000-2500	FPC	14.4w/m	12*5000mm	
LB5050-60B68	B	SMD5050	60pcs/m	465-470	1000-1500	FPC	14.4w/m	12*5000mm	
LB5050-60G68	G	SMD5050	60pcs/m	520-525	4000-5000	FPC	14.4w/m	12*5000mm	
LB5050-60W68	W	SMD5050	60pcs/m	6000±250K	6600~7200Lm	FPC	14.4w/m	12*5000mm	
LB5050-60WW68	WW	SMD5050	60pcs/m	3000±200K	6000~6600Lm	FPC	14.4w/m	12*5000mm	
LB5050-60RGB68	RGB	SMD5050	60pcs/m	523 G:520 B:4	R:600 G:1400 B:500	FPC	14.4w/m	12*5000mm	

### SMD335側發光燈條(60pcs/M)

型號 Items	顏色 Color	LED Parameters			亮度 mcd(or Lm)	材質 Material	功率 Watt/M	尺寸 Dimensions	備註 Note
		Type	Quantity	nm/K					
裸燈帶IP20									
LB335-60R	R	SMD335	60pcs/m	620-630	300-500	FPC	4.8w/m	5*1000mm	DC12V/0.4A or DC24V/0.2A, side emitting type
LB335-60Y	Y	SMD335	60pcs/m	587-592	400-600	FPC	4.8w/m	5*1000mm	
LB335-60B	B	SMD335	60pcs/m	465-470	250-300	FPC	4.8w/m	5*1000mm	
LB335-60G	G	SMD335	60pcs/m	520-525	800-1000	FPC	4.8w/m	5*1000mm	
LB335-60W	W	SMD335	60pcs/m	6000±250K	1400-1600Lm	FPC	4.8w/m	5*1000mm	

### SMD335側發光燈條(120pcs/M)

型號 Items	顏色 Color	LED Parameters			亮度 mcd(or Lm)	材質 Material	功率 Watt/M	尺寸 Dimensions	備註 Note
		Type	Quantity	nm/K					
裸燈帶IP20									
LB335-60R	R	SMD335	120pcs/m	620-630	600-1000	FPC	9.6w/m	8*1000mm	DC12V/0.8A or DC24V/0.4A, side emitting type
LB335-60Y	Y	SMD335	120pcs/m	587-592	800-1200	FPC	9.6w/m	8*1000mm	
LB335-60B	B	SMD335	120pcs/m	465-470	500-600	FPC	9.6w/m	8*1000mm	
LB335-60G	G	SMD335	120pcs/m	520-525	16-2000	FPC	9.6w/m	8*1000mm	

LB335-60W	W	SMD335	120pcs/m	6000±250K	2800-3200Lm	FPC	9.6w/m	8*1000mm
-----------	---	--------	----------	-----------	-------------	-----	--------	----------

LED為半導體發光元件，戶外使用時切忌於白天高溫時點燈使用，以確保LED壽命。



<http://www.new-wonder.com.tw> Tel:(02)2821-8897 Fax:(02)2821-4997